

Electric Forklift-Four Wheel



Normal Duty

CPD15/18/20/25/30/35/38

Item	Four Wheel Forklift (Lithium-ion) 80V (3000-7500 lbs. Capacity)							
Identification								
Series	G2 series							
Model Designation		CPD15	CPD18	CPD20	CPD25	CPD30	CPD35	CPD38
Configuration number		GB2LI-M	GB2LI-M	GB2LI-M	GB2LI-M	GB2LI-M	GB2LI-M	GB2LI-M
Load Capacity	lbs	3000	3500	4000	5000	6000	7000	7500
Load Center	in	24	24	24	24	24	24	24
Dimensions								
Overhead Guard Height	in	84.3	84.3	85.4	85.4	85.8	85.8	85.8
Overall length(without fork)	in	84.3	84.3	95.7	95.7	101.1	101.1	103.2
Overall Width	in	44.1	44.1	45.7	45.7	48.2	48.2	54.8
Min.outside turning radius	in	73.2	73.2	81.5	81.5	87.2	87.2	88.6
Performance								
Travel Speed,loaded/unloaded	mph	10.6/11.3	10.6/11.3	11.3/11.9	11.3/11.9	11.3/11.9	11.3/11.9	10.6/11.3
Lifting speed, loaded/unloaded	fpm	94.5/118.1	94.5/118.1	90.6/110.2	86.6/110.2	80.7/106.3	76.8/106.3	78.7/100.4
Max. gradeability(loaded/unloaded)	%	20/22	20/20	22/28	20/28	20/28	18/28	17/25
Controller		ZAPI	ZAPI	ZAPI	ZAPI	ZAPI	ZAPI	ZAPI
Battery Voltage/rated capacity(5h)	V/Ah	80/202	80/202	80/271	80/271	80/404	80/404	80/346
Endurance (recommended)	h	6-8	6-8	6-8	6-8	6-8	6-8	5-7
Forklift features	Main sales model. Suitable for various harsh environments. Reliable Performance. Excellent performance.							
Optional items	Large capacity lithium batteries. Fingertip control. 4-Stage mast. Cab. Cold storage. Air-conditioning, FICS. Various work lights and warning lights.							